

WP-ENL15RF

Intel Bay Trail D-J1900 Quad Core 2.0 GHz
Full IP65 Stainless Steel Panel PC



Feature

- Fanless design and compact solution
- Intel® Bay Trail Quad Core J1900 2.0GHz CPU
- Resolution 1024 x 768 dpi
- 5 wire resistive touch screen solution
- Fully IP65 compliant 6-sided stainless steel chassis
- All IP65 stainless connectors
- 1 x USB, 2 x RS232, 1 x LAN
- VESA mounting

System	
CPU	Intel® Bay Trail D-J1900 2.0GHz Quad Core Processor
Memory	1 x 204-pin DDR3L SODIMM up to 8 GB
H/W Monitor	
Watchdog Timer	256-Level Watchdog Timer
I/O Ports	
RS232	2
USB	1
GLAN	1
Storage	
Storage	1 x SATA 2.0 2.5" HDD/SSD
Expansion	
Mini-PCIe	1 x Full-size (one w/ mSATA)
Power Requirement	
Power Input Voltage	DC in 12V
Touch Screen	
Touch screen	5-wire resistive

Display	
Size	15" TFT (4:3)
Resolution	1024 x 768
Colors	16.2M
Luminance (cd/m2)	700:1
Contrast Ratio	500:1
View Angle (H / V)	160/160
Mechanical & Environmental	
Operation Temp	0 ~ 45°C
Storage Humidity	10 ~ 90%, non-condensing
Mount	VESA mounting(100X100mm)
Dimension (W x H x D mm) &Weight	380 x 290 x 67 (9.5kg)
Optional	
VGA	1
Second LAN	1
External antenna	1 or 2
RFID	1
Full IP65 Power adaptor	1

WP-ENL17RF

Intel Bay Trail D-J1900 Quad Core 2.0 GHz
Full IP65 Stainless Steel Panel PC



Feature

- Fanless design and compact solution
- Intel® Bay Trail Quad Core J1900 2.0GHz CPU
- Resolution 1280 x 1024 dpi
- 5 wires resistive touch solution
- Fully IP65 compliant 6-sided stainless steel chassis
- All IP65 stainless connectors
- 1 x USB, 2 x RS232, 1 x GLAN
- VESA mounting

System	
CPU	Intel® Bay Trail D-J1900 2.0GHz Quad Core Processor
Memory	1 x 204-pin DDR3L SODIMM up to 8 GB
H/W Monitor	
Watchdog Timer	256-Level Watchdog Timer
I/O Ports	
RS232	2
USB	1
GLAN	1
Storage	
Storage	1 x SATA 2.0 2.5" HDD/SSD
Expansion	
Mini-PCIe	1 x Full-size (one w/ mSATA)
Power Requirement	
Power Input Voltage	DC in 12V
Touch Screen	
Touch screen	5-wire resistive

Display	
Size	17" TFT (4:3)
Resolution	1280 x 1024
Colors	16.7 M
Luminance (cd/m2)	350
Contrast Ratio	1000:1
View Angle (H / V)	140/170

Mechanical & Environmental	
Operation Temp	0 ~ 45°C
Storage Humidity	10 ~ 90%, non-condensing
Mount	VESA mounting(100X100mm)
Dimension (W x H x D mm) &Weight	425 x 361 x 68 (12.5kg)

Optional	
VGA	1
Second LAN	1
External antenna	1 or 2
RFID	1
Full IP65 Power Adaptor	1

WP-ENL19RF

Intel Bay Trail D-J1900 Quad Core 2.0 GHz
Full IP65 Stainless Steel Panel PC



Feature

- Fanless design and compact solution
- Intel® Bay Trail Quad Core J1900 2.0GHz CPU
- Resolution 1280 x 1024 dpi
- 5 wires resistive touch solution
- Fully IP65 compliant 6-sided stainless steel chassis
- All IP65 stainless connectors
- 1 x USB, 2 x RS232, 1 x GLAN
- VESA mounting

System	
CPU	Intel® Bay Trail D-J1900 2.0GHz Quad Core Processor
Memory	1 x 204-pin DDR3L SODIMM up to 8 GB
H/W Monitor	
Watchdog Timer	256-Level Watchdog Timer
I/O Ports	
RS232	2
GLAN	1
USB	1
Storage	
Storage	1 x SATA 2.0 2.5" HDD/SSD
Expansion	
Mini-PCIe	1 x Full-size (one w/ mSATA)
Power Requirement	
Power Input Voltage	DC in 12V
Touch Screen	
Touch screen	5-wire resistive

Display	
Size	19" TFT (4:3)
Resolution	1280 x 1024
Colors	16.7 M
Luminance (cd/m2)	250
Contrast Ratio	1000:1
View Angle (H / V)	170/160
Mechanical & Environmental	
Operation Temp	0 ~ 45°C
Storage Humidity	10 ~ 90%, non-condensing
Mount	VESA mounting(100X100mm)
Dimension (W x H x D mm) &Weight	455X367X67(14kg)
Optional	
VGA	1
Second LAN	1
External antenna	1 or 2
RFID	1
Full IP65 Power Adaptor	1

WP-END21RF

Intel Bay Trail D-J1900 Quad Core 2.0 GHz
Full IP65 Stainless Steel Panel PC



Feature

- Fanless design and compact solution
- Intel® Bay Trail Quad Core J1900 2.0GHz CPU
- Resolution 1920 x 1080 dpi
- 5 wires resistive touch solution
- All IP65 stainless connector
- 3 x USB, 2 x RS232, 1 x LAN
- VESA mounting

System	
CPU	Intel® Bay Trail D-J1900 2.0GHz Quad Core Processor
Memory	1 x 204-pin DDR3L SODIMM up to 8 GB
H/W Monitor	
Watchdog Timer	256-Level Watchdog Timer
I/O Ports	
RS232	2
USB	3
GLAN	1
Storage	
Storage	1 x SATA 2.0 2.5" HDD/SSD
Expansion	
Mini-PCle	1 x Full-size (one w/ mSATA)
Power Requirement	
Power Input Voltage	DC in 12V
Touch Screen	
Touch screen	5-wire resistive

Display	
Size	21.5" TFT (16:9)
Resolution	1920 x 1080
Colors	16.7 M
Luminance (cd/m2)	300
Contrast Ratio	3000:1
View Angle (H / V)	178/178
Mechanical & Environmental	
Operation Temp	0 ~ 45°C
Storage Humidity	10 ~ 90%, non-condensing
Mount	VESA mounting(100X100mm)
Dimension (W x H x D mm) &Weight	561x360x67.5(15kg)
Optional	
VGA	1
Second LAN	1
External antenna	1 or 2
RFID	1
Full IP65 Power Adaptor	1